

DECKING OIL

Description:

Biohouse® Decking Oil is a wood finishing oil for protecting outdoor wooden decking, terrace or patio. It is also ideal for treating other outdoor timber such as exterior wall panel, garden furniture, summerhouse, and fencing, etc. Biohouse Decking Oil is excellent in weather resistance. The oil penetrates deeply into wood and provides excellent water-resistant and dirt repellent surface. It will not crack or peel over long period. For future renovation, no sanding is necessary. Just apply a new coat. Biohouse® Decking Oil can also be used as topcoat over outdoor satins, for example Biohouse tinted Clear Oil, as a protective layer above.

Biohouse Decking Oil is fast drying and therefore it is convenient for outdoor application considering the application and drying process must avoid rain.

We recommend to use Biohouse Decking Oil tinted with Biohouse Tinting Color for outdoor area directly exposed to sunlight, as colorless oil does not provide UV protection. Or alternatively use Biohouse UV resistant Clear Oil 8300.

Product no.:

003 – satin

Surface treatment:

Wood surface must be clean, dry and frost free, maximum moisture content 15%, old paint or varnish must be removed first.

Application:

Ready to use. Please do not thin. Stir thoroughly. 2 coats are necessary.

Use good quality bristle brush and apply one thin coat evenly along wood grain.

Second coat: after first coat 6 - 8 hours

Can also be applied with spraying gun.

Drying time: (20°C, RH50%, Provide good ventilation)

Dust dry: approx. 6 - 8 hours,

Hard dry: approx. 24hours

Final hardness after approx. 7 -14 days

Coverage:

Hardwood: 16m² / L per coat

Softwood: 10m²/L per coat

The above coverage is calculated on smooth surface. Coverage varies greatly on different wood species, surface smoothness, application method, etc.

Package:

Available in 2.5 and 20 liter tins.

Tool cleaning:

Use **biohouse® Superclean Thinner 100**.

Maintenance and renovation:

No sanding required.

Use **Biohouse® DECKING OIL** to maintain once every 1 year or when necessary depending on weathering conditions and traffic load.

Content:

modified vegetable oil, lead free siccatives, disaromatized hydrocarbon.

Pot life:

Can be stored above 3 years if can is full and tightly closed.

Caution:

Cloths impregnated with oil should be put in a bucket of water or stored in a airtight container immediately after use to eliminate any risk of spontaneous combustion common in some natural drying oils.

Stored out of the reach of children. Stored in cool place.

Disposal:

Dried product residues can be composted or put into the household waster. Liquid paint residues: EAK waste code 200112;EAK classification : paints. Packing material : Tin-plate. Empty containers can be recycled.